

Garant
Left-hand thread blind hole machine tap, TiN, Type: 15/16-16

Order data

Order number	130046 15/16-16
GTIN	4062406051020
Item class	10N

Description
Note:

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: UN-LH

Tool material: HSS E

Standard: DIN 376

Threads per inch: 16

Thread \varnothing : 23.812 mm

Overall length L: 160 mm

Shank \varnothing D_s: 18 mm

Shank square \square : 14.5 mm

Tapping hole \varnothing : 22.3 mm

Technical description

Threads per inch	16
Overall length L	160 mm
Thread \varnothing	23.812 mm
Standard	DIN 376
Thread pitch	1.588 mm
Shank square \square	14.5 mm
Tool material	HSS E
Number of cutting edges Z	4

Number of clamping slots	4
Tapping hole Ø	22.3 mm
Thread depth	47.624 mm
Shank Ø D _s	18 mm
Thread type	UN-LH
Thread size	15/16-16 UN LH
Coating	TiN
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap