

Garant
Hand tap, single Taper tap, uncoated, M: M20

Order data

| | |
|--------------|---------------|
| Order number | 130410 M20 |
| GTIN | 4062406088576 |
| Item class | 11G |

Description
Version:

3-piece set, **consisting of taper, second, and plug tap. Taper tap with long pilot.**

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 2.5 mm

Overall length L: 95 mm

Shank $\varnothing D_s$: 16 mm

Shank square \square : 12 mm

Tapping hole \varnothing : 17.5 mm

Technical description

| | |
|----------------------------|----------|
| Thread pitch | 2.5 mm |
| Tolerance class | ISO 2 6H |
| Tapping hole \varnothing | 17.5 mm |
| Thread type | M |
| Tool material | HSS E |
| Thread depth | 60 mm |
| Number of clamping slots | 3 |
| Number of cutting edges Z | 3 |
| Shank $\varnothing D_s$ | 16 mm |

| | |
|----------------------------------|---|
| Shank square □ | 12 mm |
| Standard | DIN 352 |
| Overall length L | 95 mm |
| Thread Ø | 20 mm |
| Thread size | M20 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | A |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes and through holes |
| Cutting direction | right-hand |
| Type of threading tool | Hand tap |
| Colour ring | without |
| Type of product | Tap |