

Garant
Hand tap, single Taper tap, uncoated, M: M30

Order data

Order number	130410 M30
GTIN	4062406089313
Item class	11G

Description
Version:

3-piece set, **consisting of taper, second, and plug tap. Taper tap with long pilot.**

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 3.5 mm

Overall length L: 125 mm

Shank $\varnothing D_s$: 22 mm

Shank square \square : 18 mm

Tapping hole \varnothing : 26.5 mm

Technical description

Thread pitch	3.5 mm
Thread depth	90 mm
Thread \varnothing	30 mm
Overall length L	125 mm
Shank square \square	18 mm
Tapping hole \varnothing	26.5 mm
Shank $\varnothing D_s$	22 mm
Number of cutting edges Z	3
Number of clamping slots	3

Thread type	M
Tolerance class	ISO 2 6H
Tool material	HSS E
Standard	DIN 352
Thread size	M30
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	A
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Hand tap
Colour ring	without
Type of product	Tap