

Garant
Hand tap, single Second tap, uncoated, M: M30

Order data

| | |
|--------------|---------------|
| Order number | 130420 M30 |
| GTIN | 4062406089368 |
| Item class | 11G |

Description
Version:

3-piece set, **consisting of taper, second, and plug tap. Taper tap with long pilot.**

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 3.5 mm

Overall length L: 125 mm

Shank $\varnothing D_s$: 22 mm

Shank square \square : 18 mm

Tapping hole \varnothing : 26.5 mm

Technical description

| | |
|---------------------------|----------|
| Thread type | M |
| Tolerance class | ISO 2 6H |
| Thread \varnothing | 30 mm |
| Tool material | HSS E |
| Number of cutting edges Z | 3 |
| Shank $\varnothing D_s$ | 22 mm |
| Number of clamping slots | 3 |
| Shank square \square | 18 mm |
| Overall length L | 125 mm |

| | |
|----------------------------------|---|
| Thread depth | 90 mm |
| Standard | DIN 352 |
| Tapping hole Ø | 26.5 mm |
| Thread pitch | 3.5 mm |
| Thread size | M30 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | D |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes and through holes |
| Cutting direction | right-hand |
| Type of threading tool | Hand tap |
| Colour ring | without |
| Type of product | Tap |