

Garant
GARANT Master Tap INOX machine tap HSS-E-PM Form B 6HX, TiAlN, M: M2,6

Order data

Order number	132180 M2,6
GTIN	4062406080730
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Standard:
GARANT Master Tap INOX:

powerful tap, specially developed for **tapping to high process reliability in rust-resistant and acid-resistant steels** and also **duplex materials**.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised chip flute geometry for optimum chip formation and torsional stiffness**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.45 mm

Overall length L: 50 mm

Shank \varnothing D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole \varnothing : 2.1 mm

Technical description

Shank square □	2.1 mm
Number of clamping slots	3

Overall length L	50 mm
Thread depth	7.8 mm
Tool material	HSS E PM
Tapping hole Ø	2.1 mm
Shank Ø D _s	2.8 mm
Thread type	M
Thread Ø	2.6 mm
Tolerance class	ISO 2X 6HX
Thread pitch	0.45 mm
Standard	DIN 371
Number of cutting edges Z	3
Thread size	M2.6
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap