

**Garant**
**GARANT Master Tap INOX machine tap HSS-E-PM Form B 6GX, TiAlN, M: M16**

**Order data**

Order number	132193 M16
GTIN	4062406209360
Item class	111

**Description**
**Version:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

**Tolerance class: ISO 3X/6GX.** For components which are **galvanised** or shrink slightly when hardened.

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 3X 6GX

Thread pitch: 2 mm

Overall length L: 110 mm

Shank Ø D<sub>s</sub>: 12 mm

Shank square □: 9 mm

Tapping hole Ø: 14 mm

**Technical description**

Overall length L	110 mm
Thread size	M16
Standard	DIN 376
Thread depth	48 mm
Tool material	HSS E PM

Shank $\varnothing D_s$	12 mm
Number of clamping slots	3
Number of cutting edges Z	3
Thread type	M
Shank square $\square$	9 mm
Thread $\varnothing$	16 mm
Thread pitch	2 mm
Tolerance class	ISO 3X 6GX
Tapping hole $\varnothing$	14 mm
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3xD for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap