

Garant
GARANT Master Tap INOX machine tap HSS-E-PM Form B 6GX, TiAlN, M: M6

Order data

Order number	132193 M6
GTIN	4062406209315
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Tolerance class: ISO 3X/6GX. For components which are **galvanised** or shrink slightly when hardened.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 3X 6GX

Thread pitch: 1 mm

Overall length L: 80 mm

Shank $\varnothing D_s$: 6 mm

Shank square \square : 4.9 mm

Tapping hole \varnothing : 5 mm

Technical description

Thread depth	18 mm
Shank $\varnothing D_s$	6 mm
Tapping hole \varnothing	5 mm
Thread pitch	1 mm
Tool material	HSS E PM

Shank square □	4.9 mm
Thread Ø	6 mm
Overall length L	80 mm
Thread type	M
Thread size	M6
Standard	DIN 371
Tolerance class	ISO 3X 6GX
Number of clamping slots	3
Number of cutting edges Z	3
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap