

Garant

GARANT Master Tap INOX machine tap extra long HSS-E-PM Form B 6HX, TiAlN, M: M10



Order data

Order number	132195 M10
GTIN	4062406209438
Item class	111

Description

Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

With extra long shank. Shank to DIN371.

Advantage:

Designed for tapping threads where access is difficult.

Thread type: M

Tool material: HSS E PM

Standard: Manufacturer's standard

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 200 mm

Shank $\varnothing D_s$: 10 mm

Shank square \square : 8 mm

Tapping hole \varnothing : 8.5 mm

Technical description

Thread type	M
Shank $\varnothing D_s$	10 mm
Number of clamping slots	3
Tool material	HSS E PM

Thread depth	30 mm
Shank square □	8 mm
Thread Ø	10 mm
Tolerance class	ISO 2X 6HX
Thread pitch	1.5 mm
Thread size	M10
Tapping hole Ø	8.5 mm
Standard	Manufacturer's standard
Overall length L	200 mm
Number of cutting edges Z	3
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap