

GARANT Master Tap INOX machine tap extra long HSS-E-PM Form B 6HX, TiAIN, M: M4



Order data

Order number	132195 M4
GTIN	4062406209391
Item class	111

Description

Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials.**

- · HSS-E-PM tool material for maximum wear resistance
- · The latest generation of TiALN multi-layer coating
- · Parameterised flute geometry for optimum chip formation and torsional rigidity With extra long shank. Shank to DIN371.

Advantage:

Designed for tapping threads where access is difficult.

Thread type: M

Tool material: HSS E PM

Standard: Manufacturer's standard

Tolerance class: ISO 2X 6HX

Thread pitch: 0.7 mm Overall length L: 126 mm Shank Ø D₅: 4.5 mm Shank square □: 3.4 mm Tapping hole Ø: 3.3 mm

Technical description

Thread type	M
Number of cutting edges Z	3
Overall length L	126 mm
Tool material	HSS E PM

Tapping hole Ø	3.3 mm
Tolerance class	ISO 2X 6HX
Thread size	M4
Shank square □	3.4 mm
Standard	Manufacturer's standard
Thread depth	12 mm
Number of clamping slots	3
Thread Ø	4 mm
Shank Ø D _s	4.5 mm
Thread pitch	0.7 mm
Coating	TiAIN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Тар