



Machine tap HSS-E, vaporised, M: M20



Order data

Order number	132645 M20
GTIN	4062406088156
Item class	12H

Description

Version:

Spiral point with oil grooves.

Guide section with oil grooves, but without chip flutes.

Thread type: M

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2.5 mm

Overall length L: 140 mm

Shank $\varnothing D_s$: 16 mm

Shank square \square : 12 mm

Tapping hole \varnothing : 17.5 mm

Technical description

Number of clamping slots	3
Tolerance class	ISO 2 6H
Shank square \square	12 mm
Number of cutting edges Z	3
Tapping hole \varnothing	17.5 mm
Thread type	M
Thread \varnothing	20 mm
Shank $\varnothing D_s$	16 mm

Tool material	HSS E
Thread depth	60 mm
Thread pitch	2.5 mm
Standard	DIN 376
Overall length L	140 mm
Thread size	M20
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap