

# GARANT Master Tap machine tap Form B 6HX DIN 376, AlTiX, M: M6



#### **Order data**

Order number	132726 M6
GTIN	4062406278564
Item class	111

### **Description**

#### **Version:**

**Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

**All sizes:** Shank **to DIN 376 (= shank** Ø **relieved)** thus suitable for greater operating depths.

Thread type: M

Tool material: HSS E PM Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 1 mm Overall length L: 80 mm Shank Ø D₅: 4.5 mm Shank square □: 3.4 mm Tapping hole Ø: 5 mm

## **Technical description**

Thread Ø	6 mm
Tool material	HSS E PM
Shank Ø D <sub>s</sub>	4.5 mm
Thread type	M
Number of clamping slots	3
Tapping hole ∅	5 mm

Number of cutting edges Z	3
Overall length L	80 mm
Tolerance class	ISO 2X 6HX
Thread size	M6
Thread pitch	1 mm
Standard	DIN 376
Thread depth	18 mm
Shank square □	3.4 mm
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар