

Garant**GARANT Master Tap machine tap left-hand thread HSS-E-PM 6HX, AlTiX, M-LH: M24****Order data**

Order number	132805 M24
GTIN	4062406207892
Item class	11I

Description**Version:**

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M-LH

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 3 mm

Overall length L: 160 mm

Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 21 mm

Technical description

Thread type	M-LH
Thread Ø	24 mm
Tapping hole Ø	21 mm
Tool material	HSS E PM
Tolerance class	ISO 2X 6HX

Standard	DIN 376
Shank Ø D _s	18 mm
Number of cutting edges Z	3
Thread depth	72 mm
Number of clamping slots	3
Shank square □	14.5 mm
Overall length L	160 mm
Thread pitch	3 mm
Thread size	M24 LH
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap