

Garant
GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, MF: 22X1,5

Order data

Order number	132875 22X1,5
GTIN	4062406081072
Item class	111

Description
Version:
GARANT Master Tap INOX:

Powerful tap, specially developed for **tapping to high process reliability in stainless and acid-resistant steels** and also **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 125 mm

Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 20.5 mm

Technical description

Tolerance class	ISO 2X 6HX
Number of cutting edges Z	4
Thread type	MF
Number of clamping slots	4
Thread Ø	22 mm

Standard	DIN 374
Tapping hole \varnothing	20.5 mm
Thread depth	66 mm
Tool material	HSS E PM
Shank $\varnothing D_s$	18 mm
Shank square \square	14.5 mm
Overall length L	125 mm
Thread pitch	1.5 mm
Thread size	M22 \times 1.5
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3 \times D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap