

GARANT Master Tap INOX machine tap HSS-E-PM, TiAIN, MF: 5X0,5



Order data

Order number	132875 5X0,5
GTIN	4062406080938
Item class	111

Description

Version:

GARANT Master Tap INOX:

Powerful tap, specially developed for tapping to high process reliability in stainless and acidresistant steels and also duplex materials.

- · HSS-E-PM tool material for maximum wear resistance
- · The latest generation of TiALN multi-layer coating
- · Parameterised flute geometry for optimum chip formation and torsional rigidity

Thread type: MF

Tool material: HSS E PM Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 0.5 mm Overall length L: 70 mm Shank \emptyset D_s: 3.5 mm Shank square \square : 2.7 mm Tapping hole \emptyset : 4.5 mm

Technical description

Thread Ø	5 mm
Number of clamping slots	3
Shank square □	2.7 mm
Standard	DIN 374
Tool material	HSS E PM
Tolerance class	ISO 2X 6HX

Thread pitch	0.5 mm
Thread type	MF
Shank Ø D _s	3.5 mm
Thread depth	15 mm
Number of cutting edges Z	3
Overall length L	70 mm
Tapping hole ∅	4.5 mm
Thread size	M5×0.5
Coating	TiAIN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Тар