

GARANT Master Tap machine tap HSS-E-PM, AITiX, MF: 4,5X0,5



Order data

Order number	132905 4,5X0,5
GTIN	4062406208431
Item class	111

Description

Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: MF

Tool material: HSS E PM Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 0.5 mm Overall length L: 70 mm Shank Ø D₃: 35 mm Shank square □: 27 mm Tapping hole Ø: 4 mm

Technical description

Thread pitch	0.5 mm
Thread depth	13.5 mm
Tapping hole Ø	4 mm
Standard	DIN 374
Number of clamping slots	3
Tool material	HSS E PM

Thread type	MF
Thread Ø	4.5 mm
Shank Ø D _s	3.5 mm
Shank square □	2.7 mm
Overall length L	70 mm
Number of cutting edges Z	3
Tolerance class	ISO 2X 6HX
Thread size	M4.5×0.5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар