

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, MF: 4X0,5

Order data

Order number	132905 4X0,5
GTIN	4045197984180
Item class	11I

Description
Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 0.5 mm

Overall length L: 63 mm

Shank $\varnothing D_s$: 2.8 mm

Shank square \square : 2.1 mm

Tapping hole \varnothing : 3.5 mm

Technical description

Tapping hole \varnothing	3.5 mm
Overall length L	63 mm
Tolerance class	ISO 2X 6HX
Thread depth	12 mm
Number of cutting edges Z	3
Shank $\varnothing D_s$	2.8 mm

Thread Ø	4 mm
Number of clamping slots	3
Tool material	HSS E PM
Shank square □	2.1 mm
Thread pitch	0.5 mm
Standard	DIN 374
Thread type	MF
Thread size	M4×0.5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap