



## HOLEX Pro Tap machine tap HSS-E, TiN, MF: 14X1,5



### Order data

Order number	132925 14X1,5
GTIN	4062406374051
Item class	12I

### Description

#### Version:

**HOLEX Pro Tap general-purpose tap.** Sturdy design suitable for a wide spectrum of materials.  
**Improved HSS-E tool material with low-friction TiN coating.**

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank  $\varnothing$  D<sub>s</sub>: 11 mm

Shank square  $\square$ : 9 mm

Tapping hole  $\varnothing$ : 12.5 mm

### Technical description

Thread pitch	1.5 mm
Shank $\varnothing$ D <sub>s</sub>	11 mm
Number of clamping slots	4
Tool material	HSS E
Thread type	MF
Shank square $\square$	9 mm
Tolerance class	ISO 2 6H
Number of cutting edges Z	4

Standard	DIN 374
Thread Ø	14 mm
Thread size	M14×1.5
Overall length L	100 mm
Thread depth	42 mm
Tapping hole Ø	12.5 mm
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	HOLEX Pro Tap
Type of product	Tap