



HOLEX Pro Tap machine tap HSS-E, TiN, MF: 30X1,5



Order data

Order number	132925 30X1,5
GTIN	4062406374129
Item class	12I

Description

Version:

HOLEX Pro Tap general-purpose tap. Sturdy design suitable for a wide spectrum of materials.
Improved HSS-E tool material with low-friction TiN coating.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 150 mm

Shank Ø D_s: 22 mm

Shank square □: 18 mm

Tapping hole Ø: 28.5 mm

Technical description

Thread depth	90 mm
Shank Ø D _s	22 mm
Number of cutting edges Z	4
Thread Ø	30 mm
Shank square □	18 mm
Standard	DIN 374
Tolerance class	ISO 2 6H
Overall length L	150 mm

Thread type	MF
Thread size	M30×1.5
Number of clamping slots	4
Tool material	HSS E
Tapping hole Ø	28.5 mm
Thread pitch	1.5 mm
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	HOLEX Pro Tap
Type of product	Tap