



HOLEX Pro Tap machine tap HSS-E, TiN, MF: 3X0,35



Order data

Order number	132925 3X0,35
GTIN	4062406373443
Item class	12I

Description

Version:

HOLEX Pro Tap general-purpose tap. Sturdy design suitable for a wide spectrum of materials.
Improved HSS-E tool material with low-friction TiN coating.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 0.35 mm

Overall length L: 56 mm

Shank $\varnothing D_s$: 2.2 mm

Tapping hole \varnothing : 2.65 mm

Technical description

Standard	DIN 374
Thread size	M3×0.35
Tool material	HSS E
Thread depth	9 mm
Thread \varnothing	3 mm
Overall length L	56 mm
Number of cutting edges Z	3
Number of clamping slots	3
Thread pitch	0.35 mm

Thread type	MF
Tapping hole Ø	2.65 mm
Tolerance class	ISO 2 6H
Shank Ø D _s	2.2 mm
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	HOLEX Pro Tap
Type of product	Tap