

GARANT Master Tap machine tap HSS-E-PM Form B 6HX left-hand thread, AlTiX, MF-LH: 24X1,5



Order data

Order number	133015 24X1,5
GTIN	4062406207908
Item class	111

Description

Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: MF-LH Tool material: HSS E PM Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm Overall length L: 140 mm Shank Ø D_s: 18 mm

Shank square □: 14.5 mm Tapping hole Ø: 22.5 mm

Technical description

Shank Ø D _s	18 mm
Number of cutting edges Z	3
Thread size	M24×1.5 LH
Thread type	MF-LH
Shank square □	14.5 mm

Number of clamping slots	3
Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Tapping hole Ø	22.5 mm
Thread Ø	24 mm
Thread depth	72 mm
Standard	DIN 374
Overall length L	140 mm
Thread pitch	1.5 mm
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар