

Garant
GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNC: 10-24

Order data

Order number	133356 10-24
GTIN	4062406209537
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 24

Thread Ø: 4.83 mm

Overall length L: 70 mm

Shank Ø D_s: 6 mm

Shank square □: 4.9 mm

Tapping hole Ø: 3.9 mm

Technical description

Tapping hole Ø	3.9 mm
Shank square □	4.9 mm
Standard	DIN 371
Number of cutting edges Z	3
Thread Ø	4.83 mm

Number of clamping slots	3
Thread pitch	1.058 mm
Tool material	HSS E PM
Thread depth	14.49 mm
Shank $\varnothing D_s$	6 mm
Overall length L	70 mm
Thread type	UNC
Threads per inch	24
Thread size	10-24 UNC
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap