

Garant
GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNF: 10-32

Order data

Order number	133406 10-32
GTIN	4062406209681
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity.**

Application:

For UNF uniform fine threads ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 32

Thread Ø: 4.83 mm

Overall length L: 70 mm

Shank Ø D_s: 6 mm

Shank square □: 4.9 mm

Tapping hole Ø: 4.1 mm

Technical description

Thread pitch	0.794 mm
Tapping hole Ø	4.1 mm
Threads per inch	32
Number of cutting edges Z	3
Tool material	HSS E PM

Overall length L	70 mm
Thread type	UNF
Thread Ø	4.83 mm
Shank square □	4.9 mm
Thread depth	12.075 mm
Shank Ø D _s	6 mm
Number of clamping slots	3
Standard	DIN 371
Thread size	10-32 UNF
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap