

Garant**GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNF: 3/8-24****Order data**

Order number	133406 3/8-24
GTIN	4062406209728
Item class	11I

Description**Version:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels and duplex materials.**

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity.**

Application:

For UNF uniform fine threads ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 24

Thread Ø: 9.53 mm

Overall length L: 100 mm

Shank Ø D_s: 9 mm

Shank square □: 7 mm

Tapping hole Ø: 8.5 mm

Technical description

Thread size	3/8-24 UNF
Standard	DIN 371
Thread Ø	9.53 mm
Threads per inch	24

Thread depth	23.825 mm
Thread type	UNF
Tapping hole Ø	8.5 mm
Number of clamping slots	3
Tool material	HSS E PM
Shank square □	7 mm
Shank Ø D _s	9 mm
Thread pitch	1.058 mm
Overall length L	100 mm
Number of cutting edges Z	3
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap