

Garant
GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNF: 6-40

Order data

Order number	133406 6-40
GTIN	4062406209667
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity.**

Application:

For UNF uniform fine threads ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 40

Thread Ø: 3.51 mm

Overall length L: 56 mm

Shank Ø D_s: 4 mm

Shank square □: 3 mm

Tapping hole Ø: 2.95 mm

Technical description

Thread type	UNF
Standard	DIN 371
Number of cutting edges Z	3
Shank Ø D _s	4 mm
Thread pitch	0.635 mm

Thread size	6-40 UNF
Tool material	HSS E PM
Tapping hole Ø	2.95 mm
Overall length L	56 mm
Number of clamping slots	3
Thread depth	10.53 mm
Shank square □	3 mm
Thread Ø	3.51 mm
Threads per inch	40
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap