

Garant

GARANT Master Tap INOX machine tap HSS-E-PM Form C 6HX, TiAlN, M: M10



Order data

Order number	135732 M10
GTIN	4062406081430
Item class	111

Description

Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank $\varnothing D_s$: 10 mm

Shank square \square : 8 mm

Tapping hole \varnothing : 8.5 mm

Technical description

Number of cutting edges Z	3
Standard	DIN 371
Tool material	HSS E PM
Shank square \square	8 mm
Thread pitch	1.5 mm

Shank $\varnothing D_s$	10 mm
Overall length L	100 mm
Thread \varnothing	10 mm
Thread type	M
Number of clamping slots	3
Tolerance class	ISO 2X 6HX
Thread depth	25 mm
Tapping hole \varnothing	8.5 mm
Thread size	M10
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap