

Garant

GARANT Master Tap INOX machine tap HSS-E-PM IC / Form C 6HX, TiAlN, M: M24



Order data

Order number	135734 M24
GTIN	4062406081553
Item class	11I

Description

Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

With internal coolant supply

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 3 mm

Overall length L: 160 mm

Shank $\varnothing D_s$: 18 mm

Shank square \square : 14.5 mm

Tapping hole \varnothing : 21 mm

Technical description

Thread \varnothing	24 mm
Thread depth	60 mm
Shank $\varnothing D_s$	18 mm

Tool material	HSS E PM
Tolerance class	ISO 2X 6HX
Thread type	M
Overall length L	160 mm
Number of clamping slots	4
Standard	DIN 376
Number of cutting edges Z	4
Shank square □	14.5 mm
Tapping hole Ø	21 mm
Thread pitch	3 mm
Thread size	M24
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	yes
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap