

## Garant

### GARANT Master Tap INOX machine tap HSS-E-PM Form C 6GX, TiAlN, M: M12



#### Order data

Order number	135737 M12
GTIN	4062406209858
Item class	111

#### Description

##### Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

**The 45° helix angle** of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

**Tolerance class ISO 3X/6GX.** For components which are **galvanised** or shrink slightly when hardened.

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 3X 6GX

Thread pitch: 1.75 mm

Overall length L: 110 mm

Shank  $\varnothing D_s$ : 9 mm

Shank square  $\square$ : 7 mm

Tapping hole  $\varnothing$ : 10.2 mm

#### Technical description

Shank square $\square$	7 mm
Tool material	HSS E PM
Overall length L	110 mm
Thread type	M

Tapping hole Ø	10.2 mm
Thread depth	30 mm
Number of cutting edges Z	4
Standard	DIN 376
Tolerance class	ISO 3X 6GX
Thread pitch	1.75 mm
Shank Ø D <sub>s</sub>	9 mm
Number of clamping slots	4
Thread size	M12
Thread Ø	12 mm
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap