

Garant
GARANT Master Tap INOX machine tap HSS-E-PM Form C 6GX, TiAlN, M: M4

Order data

Order number	135737 M4
GTIN	4062406209803
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Tolerance class ISO 3X/6GX. For components which are **galvanised** or shrink slightly when hardened.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 3X 6GX

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank $\varnothing D_s$: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing : 3.3 mm

Technical description

Shank square \square	3.4 mm
Thread depth	10 mm
Thread type	M
Number of cutting edges Z	3

Tool material	HSS E PM
Tapping hole Ø	3.3 mm
Thread size	M4
Number of clamping slots	3
Shank Ø D _s	4.5 mm
Overall length L	63 mm
Thread Ø	4 mm
Thread pitch	0.7 mm
Standard	DIN 371
Tolerance class	ISO 3X 6GX
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap