

## Garant

### GARANT Master Tap machine tap HSS-E-PM Form C 6HX DIN 376, AlTiX, M: M4



#### Order data

Order number	135962 M4
GTIN	4062406278601
Item class	111

#### Description

##### Version:

**Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

**All sizes: Shank to DIN 376 (= shank Ø relieved);** thus suitable for greater operating depths.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 2.8 mm

Shank square □: 2.1 mm

Tapping hole Ø: 3.3 mm

#### Technical description

Tolerance class	ISO 2X 6HX
Overall length L	63 mm
Number of clamping slots	3
Tool material	HSS E PM
Thread size	M4
Shank Ø D <sub>s</sub>	2.8 mm

Thread pitch	0.7 mm
Thread depth	10 mm
Standard	DIN 371
Thread Ø	4 mm
Shank square □	2.1 mm
Tapping hole Ø	3.3 mm
Number of cutting edges Z	3
Thread type	M
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap