

Garant**GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, MF: 12X1,5****Order data**

Order number	137053 12X1,5
GTIN	4062406081768
Item class	11I

Description**Version:****GARANT Master Tap INOX:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank Ø D_s: 9 mm

Shank square □: 7 mm

Tapping hole Ø: 10.5 mm

Technical description

Shank Ø D _s	9 mm
Thread depth	30 mm
Number of clamping slots	4
Overall length L	100 mm

Thread type	MF
Number of cutting edges Z	4
Thread pitch	1.5 mm
Tolerance class	ISO 2X 6HX
Thread Ø	12 mm
Shank square □	7 mm
Standard	DIN 374
Tapping hole Ø	10.5 mm
Tool material	HSS E PM
Thread size	M12×1,5
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap