

Garant

GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, MF: 4X0,5



Order data

Order number	137053 4X0,5
GTIN	4062406081218
Item class	111

Description

Version:

GARANT Master Tap INOX:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for a high degree of wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 0.5 mm

Overall length L: 63 mm

Shank $\varnothing D_s$: 2.8 mm

Shank square \square : 2.1 mm

Tapping hole \varnothing : 3.5 mm

Technical description

Number of clamping slots	3
Thread pitch	0.5 mm
Shank $\varnothing D_s$	2.8 mm
Thread depth	10 mm

Shank square □	2.1 mm
Tolerance class	ISO 2X 6HX
Thread type	MF
Number of cutting edges Z	3
Thread Ø	4 mm
Tapping hole Ø	3.5 mm
Overall length L	63 mm
Tool material	HSS E PM
Standard	DIN 374
Thread size	M4×0.5
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Series	GARANT Master Tap
Type of product	Tap