

Garant**GARANT Master Tap machine tap HSS-E-PM, ALTiX, MF: 10X0,75****Order data**

Order number	137160 10X0,75
GTIN	4062406219635
Item class	11I

Description**Version:**

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 0.75 mm

Overall length L: 90 mm

Shank Ø D_s: 7 mm

Shank square □: 5.5 mm

Tapping hole Ø: 9 mm

Technical description

Shank Ø D _s	7 mm
Thread Ø	10 mm
Number of clamping slots	3
Thread pitch	0.75 mm
Thread type	MF
Standard	DIN 374

Tolerance class	ISO 2X 6HX
Number of cutting edges Z	3
Tapping hole Ø	9 mm
Shank square □	5.5 mm
Tool material	HSS E PM
Thread depth	25 mm
Overall length L	90 mm
Thread size	M10×0.75
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap