Garant

GARANT Master Tap machine tap extra-long HSS-E-PM, AlTiX, MF: 10X1

tour to the tour

Order data

| Order number | 137162 10X1 |
|--------------|---------------|
| GTIN | 4062406209049 |
| Item class | 111 |

Description

Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.
- With extra long shank.

Advantage:

Designed for tapping threads where access is difficult. Thread type: MF Tool material: HSS E PM Standard: Manufacturer's standard Tolerance class: ISO 2X 6HX Thread pitch: 1 mm Overall length L: 180 mm Shank \emptyset D_s: 7 mm Shank square \Box : 5.5 mm Tapping hole \emptyset : 9 mm

Technical description

| Tapping hole Ø | 9 mm |
|---------------------------|------------|
| Thread type | MF |
| Tool material | HSS E PM |
| Tolerance class | ISO 2X 6HX |
| Number of cutting edges Z | 3 |

© Hoffmann GmbH Qualitätswerkzeuge

| | 25 |
|----------------------------------|-----------------------------------|
| Thread depth | 25 mm |
| Shank square 🗆 | 5.5 mm |
| Shank $Ø D_s$ | 7 mm |
| Thread Ø | 10 mm |
| Number of clamping slots | 3 |
| Standard | Manufacturer's standard |
| Thread size | M10×1 |
| Thread pitch | 1 mm |
| Overall length L | 180 mm |
| Coating | AlTiX |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | C |
| Helix angle | 40 degrees |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 2.5×D for blind holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for dynamic machining |
| Colour ring | green |
| Series | GARANT Master Tap |
| Type of product | Тар |
| | |