



HOLEX Pro Tap machine tap HSS-E, TiN, MF: 6X0,75



Order data

Order number	137170 6X0,75
GTIN	4062406374556
Item class	12I

Description

Version:

HOLEX Pro Tap general-purpose tap. Sturdy design suitable for a wide spectrum of materials.
Improved HSS-E tool material with low-friction TiN coating.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 0.75 mm

Overall length L: 80 mm

Shank $\varnothing D_s$: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing : 5.2 mm

Technical description

Number of clamping slots	3
Shank $\varnothing D_s$	4.5 mm
Thread size	M6x0.75
Thread depth	15 mm
Tapping hole \varnothing	5.2 mm
Thread pitch	0.75 mm
Standard	DIN 374
Shank square \square	3.4 mm

Thread type	MF
Tolerance class	ISO 2 6H
Thread Ø	6 mm
Number of cutting edges Z	3
Overall length L	80 mm
Tool material	HSS E
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	HOLEX Pro Tap
Type of product	Tap