

Garant**GARANT Master Tap INOX machine tap HSS-E-PM Form E, TiAlN, G: G5/8 inch****Order data**

Order number	137752 G5/8
GTIN	4062406210335
Item class	11I

Description**Version:****GARANT Master Tap INOX:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the chip flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Form E (1.5-2 turns lead chamfer).

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E PM

Threads per inch: 14

Thread Ø: 22.91 mm

Overall length L: 125 mm

Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 21 mm

Technical description

Shank Ø D _s	18 mm
Thread depth	57.28 mm

Number of cutting edges Z	5
Thread Ø	22.91 mm
Tool material	HSS E PM
Number of clamping slots	5
Thread pitch	1.814 mm
Threads per inch	14
Shank square □	14.5 mm
Overall length L	125 mm
Tapping hole Ø	21 mm
Thread size	G5/8
Series	GARANT Master Tap
Coating	TiAlN
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	E
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap