

Garant
GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNC: 2-56

Order data

Order number	137857 2-56
GTIN	4062406208110
Item class	111

Description
Version:

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels and duplex materials.**

- **HSS-E-PM tool material for maximum wear resistance.**
- **The latest generation of TiAlN multi-layer coating.**
- **Parameterised flute geometry for optimum chip formation and rigidity.**

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 56

Thread Ø: 2.18 mm

Overall length L: 45 mm

Shank Ø D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole Ø: 1.85 mm

Technical description

Number of clamping slots	3
Threads per inch	56
Thread type	UNC
Overall length L	45 mm
Thread depth	5.45 mm

Shank Ø D _s	2.8 mm
Thread Ø	2.18 mm
Thread size	2-56 UNC
Shank square □	2.1 mm
Number of cutting edges Z	3
Tool material	HSS E PM
Standard	DIN 371
Thread pitch	0.453 mm
Tapping hole Ø	1.85 mm
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap