

**Garant**
**GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNC: 7/8-9**

**Order data**

Order number	137857 7/8-9
GTIN	4062406210137
Item class	111

**Description**
**Version:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels and duplex materials.**

- **HSS-E-PM tool material for maximum wear resistance.**
- **The latest generation of TiAlN multi-layer coating.**
- **Parameterised flute geometry for optimum chip formation and rigidity.**

**Application:**

**For UNC uniform coarse threads ASME – B1.1.**

Thread type: UNC

Tool material: HSS E PM

Standard: DIN 376

Threads per inch: 9

Thread Ø: 22.23 mm

Overall length L: 140 mm

Shank Ø D<sub>s</sub>: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 19.5 mm

**Technical description**

Thread size	7/8-9 UNC
Thread Ø	22.23 mm
Shank Ø D <sub>s</sub>	18 mm
Shank square □	14.5 mm

Number of clamping slots	4
Tool material	HSS E PM
Threads per inch	9
Thread depth	55.575 mm
Thread pitch	2.822 mm
Number of cutting edges Z	4
Thread type	UNC
Tapping hole Ø	19.5 mm
Overall length L	140 mm
Standard	DIN 376
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap