

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, UNC: 3-48

Order data

Order number	137870 3-48
GTIN	4062406209186
Item class	11I

Description
Version:

GARANT Master Tap Universal tap, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 48

Thread Ø: 2.51 mm

Overall length L: 50 mm

Shank Ø D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole Ø: 2.1 mm

Technical description

Thread size	3-48 UNC
Thread depth	6.28 mm
Number of cutting edges Z	2
Standard	DIN 371
Thread type	UNC

Shank square □	2.1 mm
Thread pitch	0.529 mm
Thread Ø	2.51 mm
Threads per inch	48
Tool material	HSS E PM
Shank Ø D _s	2.8 mm
Tapping hole Ø	2.1 mm
Overall length L	50 mm
Number of clamping slots	2
Series	GARANT Master Tap
Coating	AlTiX
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap