

Garant**GARANT Master Tap INOX machine tap HSS-E-PM, TiAlN, UNF: 3/8-24****Order data**

Order number	138007 3/8-24
GTIN	4062406210236
Item class	11I

Description**Version:****GARANT Master Tap INOX:**

High-performance tap, specially developed for **good process reliability in stainless and acid-resistant steels** and **duplex materials**.

The 45° helix angle of the chip flutes facilitates chip formation especially in ductile austenitic CrNi steels.

- **HSS-E-PM tool material for maximum wear resistance**
- **The latest generation of TiAlN multi-layer coating**
- **Parameterised flute geometry for optimum chip formation and torsional rigidity**

Application:

For UNF uniform fine threads ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 24

Thread Ø: 9.53 mm

Overall length L: 100 mm

Shank Ø D_s: 9 mm

Shank square □: 7 mm

Tapping hole Ø: 8.5 mm

Technical description

Number of clamping slots	3
Standard	DIN 371
Thread size	3/8-24 UNF

Number of cutting edges Z	3
Thread pitch	1.058 mm
Overall length L	100 mm
Thread Ø	9.53 mm
Tapping hole Ø	8.5 mm
Thread type	UNF
Threads per inch	24
Shank Ø D _s	9 mm
Tool material	HSS E PM
Thread depth	23.825 mm
Shank square □	7 mm
Series	GARANT Master Tap
Coating	TiAlN
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	C
Helix angle	45 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap