

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, UNF: 7/16-20

Order data

Order number	138010 7/16-20
GTIN	4045197901774
Item class	111

Description
Version:

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Application:

For UNF uniform fine threads ASME – B1.1.

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 374

Threads per inch: 20

Thread Ø: 11.11 mm

Overall length L: 100 mm

Shank Ø D_s: 8 mm

Shank square □: 6.2 mm

Tapping hole Ø: 9.9 mm

Technical description

Standard	DIN 374
Thread pitch	1.27 mm
Thread type	UNF
Tool material	HSS E PM
Threads per inch	20

Thread size	7/16-20 UNF
Thread depth	27.78 mm
Overall length L	100 mm
Shank square □	6.2 mm
Tapping hole Ø	9.9 mm
Number of cutting edges Z	3
Thread Ø	11.11 mm
Number of clamping slots	3
Shank Ø D _s	8 mm
Series	GARANT Master Tap
Coating	AlTiX
Flank angle	60 degrees
Tolerance class	2BX
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap