

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, NPT: 1/16-27

Order data

Order number	138105 1/16-27
GTIN	4045197984371
Item class	111

Description
Version:

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum chip evacuation.**

Application:

Tapered pipe threads (NPT) to **ANSI B1.20.1**, for threads with sealants. See the table for the specified minimum size of the tapping hole.

Recommendation:
Tapping hole Ø A:

Pre-drill a plain hole **without using a reamer**.

Tapping hole Ø B:

Pre-drill a plain hole and then **ream it using a 1:16 taper reamer (see No. 162650)**. The taper bore Ø B can then be checked laterally by reference to the D_{max} check dimension (see table). **Variant B** for drilling the tapping hole offers the best process reliability for the tapping operation.

Threads per inch: 27

Overall length L: 90 mm

Shank Ø D_s : 6 mm

Shank square □: 4.9 mm

Tapping hole Ø A: 6.15 mm

Tapping hole Ø B: 5.95 mm

Technical description

Shank square □	4.9 mm
----------------	--------

Number of cutting edges Z	3
Thread depth	15.8 mm
Thread pitch	0.941 mm
Thread size	1/16-27
Threads per inch	27
Tapping hole Ø B	5.95 mm
Thread gauge Ø D _{max} + 0.05	6.39 mm
Number of clamping slots	3
Tapping hole minimum depth	12 mm
Tapping hole Ø A	6.15 mm
Thread Ø	7.895 mm
Overall length L	90 mm
Shank Ø D _s	6 mm
Coating	AlTiX
Thread type	NPT
Flank angle	60 degrees
Tool material	HSS E PM
Standard	Manufacturer's standard
Thread standard	ANSI B 1.20.1
Taper lead form	C
Taper ratio	1:16
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	for blind hole and through hole
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap

Type of product

Tap