

## Garant

### GARANT Master Tap machine tap for wire thread inserts HSS-E-PM, AlTiX, EG-M: EG-M3



#### Order data

Order number	138210 EG-M3
GTIN	4062406208875
Item class	111

#### Description

##### Version:

**Tap to DIN 40435 (similar to DIN 371 / DIN 376).**

**GARANT Master Tap Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

##### Application:

For production of AC mounting thread to metric ISO threads **DIN 8140** for **STI** (Screw Thread Insert) wire thread inserts.

##### Note:

Please ensure without fail to state the correct **tapping drill Ø (see table)!**

Tool material: HSS E PM

Standard: DIN 40435

Tolerance class: 6HX mod.

Thread pitch: 0.5 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 4.5 mm

Shank square □: 3.4 mm

Tapping hole Ø: 3.15 mm

#### Technical description

Overall length L	63 mm
Thread Ø	3 mm

Thread size	M3
Shank $\varnothing D_s$	4.5 mm
Standard	DIN 40435
Thread pitch	0.5 mm
Tapping hole $\varnothing$	3.15 mm
Thread depth	9 mm
Tolerance class	6HX mod.
Shank square $\square$	3.4 mm
Tool material	HSS E PM
Number of clamping slots	3
Number of cutting edges Z	3
Coating	AlTiX
Thread type	EG-M
Flank angle	60 degrees
Taper lead form	E
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap