



Fluteless machine tap without oil grooves HSS-E 6HX, TiAlN, M: M1,6



Order data

Order number	139132 M1,6
GTIN	4045197446473
Item class	12H

Description

Version:

Size M1 - M1.4– **tolerance class:** ISO 1X / 4HX

DIN 2174 (\approx **DIN 371** \leq M10; \approx **DIN 376** \geq M12).

Tolerance class: ISO 2X 6HX

Thread pitch: 0.35 mm

Overall length L: 40 mm

Shank $\varnothing D_s$: 2.5 mm

Shank square \square : 2.1 mm

Tapping hole \varnothing with guide value: 1.45 mm

Technical description

Thread pitch	0.35 mm
Thread \varnothing	1.6 mm
Number of cutting edges Z	3
Number of clamping slots	3
Shank $\varnothing D_s$	2.5 mm
Shank square \square	2.1 mm
Overall length L	40 mm
Tapping hole \varnothing with guide value	1.45 mm
Tolerance class	ISO 2X 6HX
Thread depth	2.4 mm
Thread size	M1.6

Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5xD for blind holes and through holes
Cutting direction	right-hand
Colour ring	green
Type of product	Fluteless tap