

## Garant

### GARANT Master Form Steel fluteless machine tap with oil grooves HSS-E-PM Form C 6HX, TiAlN, M: M5



#### Order data

Order number	139194 M5
GTIN	4062406381172
Item class	111

#### Description

##### Version:

The latest generation of **high-performance fluteless taps**, specially developed for **use in steel materials**.

- **Optimised polygon geometry for a lower torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for exceptional process reliability.**

**DIN 2174** (≈ DIN 371 ≤ M10; ≈ DIN 376 ≥ M12).

**Tolerance class:** ISO 2X/6HX.

Tolerance class: ISO 2X 6HX

Thread pitch: 0.8 mm

Overall length L: 70 mm

Shank Ø D<sub>s</sub>: 6 mm

Shank square □: 4.9 mm

Tapping hole Ø guide value: 4.65 mm

#### Technical description

Shank square □	4.9 mm
Thread depth	15 mm
Overall length L	70 mm
Tolerance class	ISO 2X 6HX
Shank Ø D <sub>s</sub>	6 mm
Number of cutting edges Z	5

Thread size	M5
Series	GARANT Master Steel
Tapping hole Ø guide value	4.65 mm
Thread Ø	5 mm
Thread pitch	0.8 mm
Number of clamping slots	5
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap