

Garant
Fluteless machine tap with oil grooves HSS-E-PM Form E 6HX, TiAlN, M: M10

Order data

Order number	139198 M10
GTIN	4062406383435
Item class	111

Description
Version:

The latest generation of **high-performance fluteless taps**, specially developed for **use in steel materials**.

- **Optimised polygon geometry for a lower torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for exceptional process reliability.**

DIN 2174 (\approx DIN 371 \leq M10; \approx DIN 376 \geq M12).

Tolerance class: ISO 2X/6HX.

Form E (lead-in 1.5 – 2 turns) **for deep threads with short run-out.** The thread is tapped almost to the bottom of the hole.

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank \varnothing D_s: 10 mm

Shank square □: 8 mm

Tapping hole \varnothing guide value: 9.35 mm

Technical description

Thread depth	30 mm
Overall length L	100 mm
Number of clamping slots	6
Thread pitch	1.5 mm
Number of cutting edges Z	6

Thread size	M10
Tapping hole \varnothing guide value	9.35 mm
Shank \varnothing D _s	10 mm
Series	GARANT Master Steel
Tolerance class	ISO 2X 6HX
Shank square \square	8 mm
Thread \varnothing	10 mm
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	E
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap