

Garant

Fluteless machine tap with oil grooves HSS-E-PM Form E 6HX, TiAlN, M: M2,5



Order data

Order number	139198 M2,5
GTIN	4062406383367
Item class	111

Description

Version:

The latest generation of **high-performance fluteless taps**, specially developed for **use in steel materials**.

- **Optimised polygon geometry for a lower torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for exceptional process reliability.**

DIN 2174 (\approx DIN 371 \leq M10; \approx DIN 376 \geq M12).

Tolerance class: ISO 2X/6HX.

Form E (lead-in 1.5 – 2 turns) **for deep threads with short run-out.** The thread is tapped almost to the bottom of the hole.

Tolerance class: ISO 2X 6HX

Thread pitch: 0.45 mm

Overall length L: 50 mm

Shank \varnothing D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole \varnothing guide value: 2.3 mm

Technical description

Number of cutting edges Z	4
Shank \varnothing D _s	2.8 mm
Thread pitch	0.45 mm
Series	GARANT Master Steel
Shank square □	2.1 mm

Number of clamping slots	4
Tolerance class	ISO 2X 6HX
Thread size	M2.5
Thread depth	7.5 mm
Tapping hole Ø guide value	2.3 mm
Thread Ø	2.5 mm
Overall length L	50 mm
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	E
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap