

## Garant

### Fluteless machine tap with oil grooves HSS-E-PM IC / Form C 6HX, TiAlN, M: M10



#### Order data

Order number	139202 M10
GTIN	4062406383497
Item class	111

#### Description

##### Version:

The latest generation of **high-performance fluteless taps**, specially developed for **use in steel materials**.

- **Optimised polygon geometry for a lower torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for exceptional process reliability.**

**DIN 2174 (≈ DIN 371 ≤ M10; ≈ DIN 376 ≥ M12). With oil grooves; optimum lubrication effect even in deeper threads.**

**Tolerance class:** ISO 2X/6HX.

**With internal coolant feed laterally from the grooves.** Permits the longest possible tool life when machining through holes and blind holes.

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank Ø D<sub>s</sub>: 10 mm

Shank square □: 8 mm

Tapping hole Ø guide value: 9.35 mm

#### Technical description

Number of cutting edges Z	6
Tapping hole Ø guide value	9.35 mm
Thread depth	30 mm
Shank Ø D <sub>s</sub>	10 mm

Shank square <input type="checkbox"/>	8 mm
Thread size	M10
Overall length L	100 mm
Number of clamping slots	6
Thread Ø	10 mm
Series	GARANT Master Steel
Thread pitch	1.5 mm
Tolerance class	ISO 2X 6HX
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	yes
Application for type of drilling	up to 3xD for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap