

Garant

Fluteless machine tap with oil grooves extra long HSS-E-PM Form C 6HX, TiAlN, M: M12



Order data

Order number	139208 M12
GTIN	4062406383732
Item class	11I

Description

Version:

The latest generation of **high-performance fluteless taps**, specially developed for **use in steel materials**.

- **Optimised polygon geometry for a lower torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for exceptional process reliability.**

Tolerance class: ISO 2X/6HX.

With extra long shank.

Advantage:

Ideal for thread forming where access is difficult.

Tolerance class: ISO 2X 6HX

Thread pitch: 1.75 mm

Overall length L: 220 mm

Shank $\varnothing D_s$: 9 mm

Shank square \square : 7 mm

Tapping hole \varnothing guide value: 11.2 mm

Technical description

Series	GARANT Master Steel
Shank $\varnothing D_s$	9 mm
Thread depth	36 mm
Number of clamping slots	8
Shank square \square	7 mm

Thread Ø	12 mm
Thread pitch	1.75 mm
Thread size	M12
Tapping hole Ø guide value	11.2 mm
Number of cutting edges Z	8
Tolerance class	ISO 2X 6HX
Overall length L	220 mm
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	Manufacturer's standard
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap