

Garant

Synchronised fluteless machine tap with oil grooves HSS-PMIC / Form C, TiN, M: M16



Order data

Order number	139230 M16
GTIN	4062406088330
Item class	11H

Description

Version:

Special polygon geometry and shank to DIN 1835-B for machines with **synchronised spindle drive**. **With oil grooves; optimal lubrication effect even in deeper threads.**

The **innovative polygon form** permits a wide application spectrum. The **multi-function layered coating** achieves **maximum service life** even in **high-tensile materials** in **fixed applications**.

With internal coolant supply laterally from the grooves; permits maximum tool life.

Note:

For use on synchronised spindles, the **GARANT** quick-change tapping chuck **No. 338100 – 338121 with minimum length adjustment (MLA)** ensures the highest process reliability.

Tolerance class: ISO 2X 6HX

Thread pitch: 2 mm

Overall length L: 110 mm

Shank $\varnothing D_s$: 12 mm

Shank square \square : 9 mm

Tapping hole \varnothing with guide value: 15.1 mm

Technical description

Thread depth	40 mm
Shank $\varnothing D_s$	12 mm
Number of cutting edges Z	5
Thread pitch	2 mm
Shank square \square	9 mm

Thread Ø	16 mm
Overall length L	110 mm
Taper lead angle	8 degrees
Number of clamping slots	5
Tapping hole Ø with guide value	15.1 mm
Tolerance class	ISO 2X 6HX
Thread size	M16
Coating	TiN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	Manufacturer's standard
Thread standard	DIN 13
Taper lead form	C
Shank	DIN 1835 B with h6
Through-coolant	yes
Application for type of drilling	up to 2.5xD for blind holes and through holes
Cutting direction	right-hand
Shank tolerance	h6
Colour ring	green
Type of product	Fluteless tap