

Garant
GARANT Master Form Steel fluteless machine tap with oil grooves HSS-E-PM, TiAlN, MF: 4X0,5

Order data

Order number	139280 4X0,5
GTIN	4062406375119
Item class	11I

Description
Version:
GARANT Master Form Steel:

The latest generation of **high-performance fluteless taps** are specially developed for **use in steels**.

- **Optimised polygon geometry for a reduced torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for top process reliability.**

DIN 2174 (≈ DIN 371 ≤ M10; DIN 376 ≥ M12).

Tolerance class: ISO 2X 6HX

Thread pitch: 0.5 mm

Overall length L: 63 mm

Shank Ø D_s: 4.5 mm

Shank square □: 3.4 mm

Tapping hole Ø guide value: 3.8 mm

Technical description

Thread size	M4×0.5
Tolerance class	ISO 2X 6HX
Shank square □	3.4 mm
Thread Ø	4 mm
Tapping hole Ø guide value	3.8 mm

Thread pitch	0.5 mm
Number of clamping slots	5
Shank Ø D _s	4.5 mm
Overall length L	63 mm
Thread depth	12 mm
Series	GARANT Master Steel
Number of cutting edges Z	5
Coating	TiAlN
Thread type	MF
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap